



Personal computers



Small computers network



Local Area Networks (LAN)



Workstations



Servers



EPOS (Electronic Point Of Sales) system



Data Centers



Industrial PLCs



Cash registers



Electro-medical devices



Emergency devices (lights/alarms)



Telecommunication devices



e-Business (Server Farms, ISP/ASP/POP)



Industrial processes

DIALOG PLUS RACK

700 - 3000 VA
single-phase

DIALOG PLUS RACK

NET-TEL Range



For outstanding power protection and communication **DIALOG PLUS RACK** is the best solution for sensitive and "mission-critical" applications.

The **DIALOG PLUS RACK** series comprises the 700-1000-1500-2200-3000VA models and uses double conversion technology (VFI). The load is powered continuously by the inverter with an EMI filtered, stabilised and regulated sinewave supply.

The input and output EMI filters considerably increase the immunity of the load to mains disturbances and surges, even on bypass. The UPS can power the load for long periods (using battery extension packs) or provide sufficient runtime to allow shut-down of the protected computer systems using the **PowerShield²** software, supplied as standard, for Windows 95, 98, Me, 2000, 2003, XP, Mac OS 9.x, X, Linux, NT 4.0, Novell operating systems.

DIALOG PLUS RACK -ER models are supplied with a larger internal charger and with their matching external battery extension packs can achieve long back up times.

CHARACTERISTICS

- Reliable, stabilised, filtered voltage double on-line conversion technology (VFI according to EN62040-3 specifications) with filters for the suppression of atmospheric disturbances
- high overload capability (up to 150%)
- auto restart when mains power returns (programmable)
- GS-TÜV certification
- power factor correction with sinusoidal input to ensure a low impact on the mains supply (UPS input power factor, close to 1)
- wide input voltage range (110-300Vac) to reduce battery usage
- integrated protection for PC networks and telephone line/modem connections RJ45-RJ11
- option to extend the back up time to several hours
- programming of operating functions via software
- timer for scheduled shut-down (software programmable)
- high level reliability of the batteries (automatic and manual test)
- high level reliability of the UPS (full microprocessor control)
- breaker based input protection.

ADVANCED COMMUNICATION

- Advanced, multi-platform communication for all operating systems and network environments: **PowerShield²** supervision and shut-down software included, with SNMP agent, for Windows 95, 98, NT 4.0, Me, 2000, 2003, XP, Novell, Linux, Mac OS 9.x, Mac OS X operating systems. The UPS is supplied with a communication cable for Plug and Play PC connection
- UPS tools configuration software
- Emergency Power Off (EPO) contact
- RS232 serial port
- slot-in SNMP network adapter card.

2-YEAR WARRANTY

MODELS	DLPR 70	DLPR 100	DLPR100 ER	DLPR 150	DLPR 220	DLPR220 ER	DLPR 300	DLPR300 ER
POWER	700VA / 490W	1000VA / 700W		1500VA / 1050W	2200VA / 1540W		3000VA / 2100W	
INPUT								
Rated voltage	220 - 230 - 240 Vac							
Minimum input range	110V up to 60% of load/120V from 60% to 70% of load 140V from 70 to 80% of load/160V from 80% to 100% of load							
Maximum input range	300 V							
Rated frequency	50/60 Hz ± 5Hz							
Rated current (A)	2.5	3.5	5.2	6.8	10	13.8	14.4	16
Power factor	> 0.97							
BY PASS								
Voltage tolerance	static ± 1.5%							
Frequency tolerance	± 0,5%							
BATTERIES								
Type	VRLA AGM Maintenance-free lead-acid							
Recharge time	4 h							
OUTPUT								
Rated voltage	220 or 230 or 240 Vac selectable ± 1,5%							
Waveform	Sinewave							
Voltage distortion	< 2%							
Frequency	50 or 60 Hz selectable							
Frequency tolerance	± 0,5 %							
Crest factor (Ipeak/Irms)	3 : 1 (up to 100% of load)							
Overload	110% 30'; 130% 30"; 150% 10"							
Output sockets	4 IEC 320 10A						4 IEC 320 10A + 1 IEC 320 16A	
ENVIRONMENTAL								
Weight (kg)	13	16	9	21	30	13	31	14
Dimensions (hwd) (mm)	2Ux19"x390			2Ux19"x480	3Ux19" x560	2Ux19" x480	3Ux19" x560	2Ux19" x480
AC/AC Efficiency	90%							
Communication	RS232 + communication interface slot							
Operating temperature	0 °C - 40 °C, ideal for battery 15 °C - 25 °C							
Relative humidity	< 95% non condensing							
Protection	Overload - short-circuit - overvoltage - undervoltage - temperature - low battery							
Safety compliance	EN 62040-1 EMC EN 62040-2 Directives 73/23-93/68-89/336 EEC EN 62040-3							
Surge capability	3KA 8/20 µs							
Colour	Dark grey RAL 5004							
Noise	<40 dBA at 1 m							
OPTIONS								
Extended runtime solutions	—	yes						
External manual bypass (hwd) mm/kg	2Ux438x360 - rack version weighs 6,8 (see Multipass) 180x300x115 - box version weighs 3,3 (see Multipass)							

Product characteristics can be customised to meet client specifications.

DETAILS

